

NVR3104-P4-S3

Smart265/264 4CH 4K POE NVR



Key Features

- Support Smart265/264 video formats
- 4-channel input
- Third-party IP cameras supported with O-N-V-I-F conformance: Profile S, Profile G, Profile T
- Support 1-ch HDMI, 1-ch VGA
- HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDD up to 8TB
- Support cloud upgrade

Technical Specifications:

Video/Audio Input	
IP Video Input	4-ch
Network	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	48Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 4k(3840x2160@30),4k(3840x2160@60),1024X768@60,1280X720@60,1280X1024@60,1920X1080@50,1920X1080@60
	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	4-ch
Decoding	
Decoding format	Smart265/264
Liveview/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 1 x 5MP@30, 2 x 4MP@30, 4 x 3MP@25, 4 x 1080p@30
Hard Disk	



SATA	1 SATA interface
Capacity	up to 8TB for each disk
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
PoE Interface	
Interface	4 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port
	Max 54W in total
Supported Standard	IEEE 802.3at, IEEE 802.3af
General	
Power Supply	48V DC
	Power Consumption: ≤ 9 W (without HDD)
Working Environment	-10°C ~ +55°C (+14°F ~ +131°F), Humidity $\leq 90\%$ RH (non-condensing)
Dimensions (WxDxH)	260mm x 240mm x 46mm (10.2"x9.4"x1.8")
Weight (without HDD)	1.1kg (2.43 lb)

