
Standard Operating Procedure (SOP)				
How to Cleanup the Water Mist of Camera				
Product name PG2087C				
Preparations & Procedures				
Content	P1 Prepare tools and check the	Prepare tools and check the outlook of camera		
	P2 Disassemble the camera	Disassemble the camera		
	P3 Dryout the water mist inside	Dryout the water mist inside		
	P4 Re-assemble the camera	Re-assemble the camera		
P1: Prepare tools and check the outlook of camera				
Step	Instructions	Image Reference		
1	A camera with water mist problem in front lens;			
2	Tools you need: cross screwdriver, dust-free rag( clean paper towel) desiccant hair dryer			
3	Pull the black case outward	And see		



P4:Re-assemble the Camera		
3	Replace the desiccant: roll up the desiccant and put it into the camera	
2	Use the hair dryer to dryout the front and back cover and inside parts	
1	Use a dust-free cloth or a clean paper towel to wipe off the water mist and dirty spots on the lens cover to ensure that the lens cover is clean (please wipe carefully to avoid scratches)	

1	assembly: Check the water mist and dirty spots on the front lens cover again, and then tighten the 3 screws. And put the camera chip in the case	
2	Tighten the fixing screw between the front cover of the lens and the housing	
3	Check the waterproof rubber ring between the lens and the housing, and close the black housing	