PG Camera P2P Settings

1.First connect the camera to the switch (or router) with a network cable, connect the computer network cable to the same switch (or router), download the search software AjDevTools from the computer, search, select the camera and modify the IP address of the same network segment as the computer.

AJ DEVICE TOOLS	FOR SEARCH	ING/CONFIGURING/U	JPGRADDING	V5.3.14_20	220722	in a										10.0	20	© ×
All SetCard	All NetCards	▼ Start Search	Expart to E	admin	123456	QR code 🕅	Audio 📝 Full serv	on switching stress									Total:	1 Seleted:
P Address 100, 100, 1, 100	HTTP	Medel T	tle Nume	Firmware	Versien		AF Status			All subn	SH.	Setnusk	Rac	Cloud se	Cloud servi	Duning time	NetCard	Cloud Ser
1 182.100.1.125		WESTOTIKE C	uver u	100300100	_F2 10. 0.0_220020 1	00110 2022 00 20	Login Soice	13		THEOLY	17000000000000	200.200.200.0	10.00.00.00.01.01	Papers	08140251214	10 1000 35	186.1	ottenne
1																		
				1														
				/														
			1															
			1															
			1															
			/															
								ш										
Batch Reset	Jatch Reb	If Batch Sett	ing Batch S and and	io encede	All submet ONVIF	Batch Tining Waintenance	Video sindov	print label	Batch xet ai detect									
Upgrude Firmare C:Wysers\Public\Documents				Batch Set Language	Batch Set Flatform													
Nggrade urwware by C:Wsers'Public/Documents path SOUZ/60HZ Jatch Snap Ficture Ca				Centrel IO Output	Audio													
Vpload Browse Batch D Con				Batch Bownload	Batch Set Title	Batch Botico.	Factory Rode											

2. Open the browser and enter the IP address of the camera, enter the web login interface, the default user name is admin, and the default password is 123456.

- C Lune (1903 190 1 196)	2 0 - d (+ 1		0.0
(0, 10, http://142.106.1.123)	S D C B Login	X	W 1
			1
			1
			1
			1
			1
			1
			1
			1
			1
			1
			1
			1
			1
			1
	IP Camera Web Login		1
			1
			1
	admin admin		
	P T		
	Language: English		1
			1
			1
	Login		1
			1
			1
			1
			1
			1
			1
			1
			1
			1

3.After successful login, click Settings, find Network-P2P, Enable-Save, wait for 3-5 minutes to generate a QR code, the status is online, use the mobile VideoLink APP to scan the code to add.

